

Vehicle model	DAILY 3.0 35S15 / 35C15 / 40C15 / 45C15 / 50C15 / 60C15 / 65C15 / 70C15 / 72C15 35S18 / 35C18 / 40C18 / 45C18 / 50C18 / 60C18 / 65C18 / 70C18 / 72C18 35S14 / 35C14 / 40C14 / 50C14 / 60C14 / 65C14 / 70C14 / 72C14 - CNG / NPW	DAILY 3.0 35S15 / 35C15 / 50C15 / 65C15 / 70C15 35S17 / 35C17 / 50C17 / 65C17 / 70C17	
Year	(09/2014>)	(09/2014>)	
Engine Type	F1CFL411E*A / F1CGL411E*A / F1CGL411A*E (Euro 6) F1CFL411F*A / F1CGL411F*A / F1CGL411B*E (Euro 6) F1CFA401A*A (CNG)	F1CFL411J*C (Euro 5b+) F1CFL411H*C (Euro 5b+)	
CV(kW) @ rpm	150 (110) @ 800 180 (132) @ 800 136 (100) @ 800 (methanol supply)	146 (107) @ 3.500 170 (125) @ 3.500	
N. of cylinders/cm3	4 / 2.998	4 / 2.998	
Volts	12	12	
Air Conditioning	Vehicles with or without A/C	Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	
Compressors type	25cc: 236F5H25D10 IPH	25cc: 236F5H25D10 IPH	
Comments	<ul style="list-style-type: none"> - Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 - Can be fit on AWD vehicles - It is required to purchase the fan channeler IVECO ref. 5802725496. - Mandatory increase of engine idle speed to 1150 rpm. Operation to be done in an official Iveco Dealer. 	<ul style="list-style-type: none"> - Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 - Can be fit on AWD vehicles - It is required to purchase the fan channeler IVECO ref. 5802725496. - Mandatory increase of engine idle speed to 1150 rpm. Operation to be done in an official Iveco Dealer. 	
Clutch type	Without clutch pulley	Without clutch pulley	
	Poly-V 8K Ø133 932 rpm	Poly-V 8K Ø133 932 rpm	
Kit No.	KH15017003	KH15017003	
Last update	2019-07-12	2019-07-12	